

7 Kayleigh Drive, Maroochydore Qld 4558 Phone: 07 5443 2111

20 Rene Street, Noosaville, Qld 4566 Phone: 07 5449 7855

134 Bulcock Street, Caloundra, Qld 4551 Phone: 07 5438 1588

QBCC License No: 69021 QBuild Registration No: 878105

Lo-Chlor IRON STAIN REMOVER



DIRECTIONS FOR USE:

- Allow Free Chlorine level to fall below 0.5 PPM by switching off the Salt Chlorinator or using Lo-Chlor CHLORINE REMOVER.
- Adjust pH to 7.2 to 7.6.
- Add 1 Kg of Lo-Chlor IRON STAIN REMOVER per 50,000 litres pool water with pump and filter running.
- Products may be **sprinkled directly** over stained areas or **evenly distributed** around the pool.
 - CAUTION: When using in QUARTZON, COLOURED PEBBLE, COLOURED MARBLE, EXPOSED AGGREGATE finishes or PRINTED VINYL LINERS do not allow direct contact with the pool surface. In these cases it is recommended that you MIX IT IN A BUCKET OF WATER and DISPERSE AROUND THE POOL EVENLY.
- Run pump and filter for a minimum of 24 hours then resume normal filtration.
- Pool water must be re-balanced following use of Lo-Chlor IRON STAIN REMOVER
- Consult your pool professional for advice on re-balancing pool water

SPOT STAINING

For less severe **SPOT STAINING** we recommend that you add a small amount of **Lo-Chlor IRON STAIN REMOVER** to a sock or stocking then attach to the end of a telepole and dangle **close to but not directly touching the stain** and see if this removes the stain. If no sign of improvement is shown after a few minutes, revert to procedure as above.

Most IRON STAINING forms due to INCORRECTLY BALANCED WATER



